## Push ☐30 Push Button Switches

## □30 Square Push Button Switches (SQ3PFS Series)

Туре	Appearance	Model	Contact block		LED block	
Type	Appearance	Model	A contact	B contact	AC/DC voltage	AC voltage
Flush		SQ3PFS-P1□A(M)	1	_		
		SQ3PFS-P1□2A(M)	2	_		
		SQ3PFS-P1□3A(M)	3	_		
		SQ3PFS-P1□B(M)	_	1		
		SQ3PFS-P1□2B(M)	_	2	]_	-
		SQ3PFS-P1□3B(M)	_	3		
		SQ3PFS-P1□AB(M)	1	1		
		SQ3PFS-P1□2AB(M)	2	1		
		SQ3PFS-P1□A2B(M)	1	2		
	SQ3PFS-P1K□	**The control unit, contact blocks (control unit: bold letters, contact blocks)				
		Dimensions				(unit: mm)
		30.4 3.7	Panel thickness: Ma	B 99.4	Singular typ Modular typ	pe 57.4 25.0
	※For panel cut-out dimensions, please refe					eter to page A-104.

A-102 **Autonics** 

Ø16

	ļ				Contact block		LED block	
Туре	Appearance		Model	A contact	B contact	AC/DC voltage	AC voltage	
Flush (illuminated)		Standard	SQ3PFS(U)-P3□AD(M)	1	_		-	
			SQ3PFS(U)-P3□2AD(M)	2	_			
			SQ3PFS(U)-P3□BD(M)	_	1	1		
			SQ3PFS(U)-P3□2BD(M)	_	2			
			SQ3PFS(U)-P3□ABD(M)	1	1			
			SQ3PFS(U)-P3□AL(M)	1	_	_	1	
			SQ3PFS(U)-P3□2AL(M)	2	_			
			SQ3PFS(U)-P3□BL(M)	_	1			
			SQ3PFS(U)-P3□2BL(M)	_	2			
			SQ3PFS(U)-P3□ABL(M)	1	1			
			SQ3PFS-P3□LAD(M)	1	_			
			SQ3PFS-P3□L2AD(M)	2	_	-	_	
			SQ3PFS-P3□LBD(M)	_	1	1		
	The state of the s		SQ3PFS-P3□L2BD(M)	_	2			
	The same of the sa	Arrows	SQ3PFS-P3□LABD(M)	1	1			
	SQ3PFS-P3Y□	(Left/ Right)	SQ3PFS-P3□LAL(M)	1	_			
		rtigiit)	SQ3PFS-P3□L2AL(M)	2	_			
			SQ3PFS-P3□LBL(M)	_	1	1_	1	
			SQ3PFS-P3□L2BL(M)	_	2			
	- United		SQ3PFS-P3□LABL(M)	1	1			
	The state of the s	Arrows (Up/ Down)	SQ3PFS-P3□UAD(M)	1	_		_	
	SQ3PFSU-P3Y□  SQ3PFS-P3YU□		SQ3PFS-P3□U2AD(M)	2	_			
			SQ3PFS-P3□UBD(M)	_	1	1		
			SQ3PFS-P3□U2BD(M)	_	2	-		
			SQ3PFS-P3□UABD(M)	1	1			
			SQ3PFS-P3□UAL(M)	1	·		1	
			SQ3PFS-P3□U2AL(M)	2	1_			
			SQ3PFS-P3□UBL(M)	_	1			
			SQ3PFS-P3□U2BL(M)	_	2			
			SQ3PFS-P3□UABL(M)	1	1			
		*Models with the Models with the Models with the control with the control with the models with the control with the contro	tes color: R, B, G, Y, W without 'U' in the model name in the model name indicates mo plock. trol unit, contact blocks, LED b unit: bold letters, contact and it	odular type cor blocks are sold LED block: reg	ntact block. Mo	he button cap. dels without M are	e singular	
		Dimension				(unit: mm)		
		1.84	3.7	Panel thickness	B	Singular type Modular type	57.4 25.0	
				※For panel	cut-out dimens	sions, please refer	to page A-104.	

**Autonics** A-103

## **□30 Pilot Lights (LQ3RF Series)**

Туре	Appearance	Model	Contact block		LED block				
		Model	A contact	B contact	AC/DC voltage	AC voltage			
-lat square		<b>LQ3RF-L4</b> □D(M)			1	_			
flush)		LQ3RF-L4□L(M)		-	_	1			
		<ul><li>**The M in the model n block.</li><li>**The light unit and LEI</li></ul>	<ul> <li>※☐ indicates color: R, B, M, W</li> <li>※The M in the model name indicates modular type LED block. Models without M are singular LED block.</li> <li>※The light unit and LED blocks are sold separately. (light unit: bold letters, LED block: regular letters)</li> <li>※The LED color is the same as the control unit.</li> </ul>						
		Dimensions	Panel thickness	s: Max. 6mm		(unit: mm)			
	LQ3RF-L4B□	1.89	38	39.4					
					Singular ty	A B pe 59.4 27.0			
		_	1.1	B .	Orrigalar ty	27.0			

## **□30 Panel Cut-out Dimensions**

(unit: mm)

Туре		A	В	Panel Cut-out Dimensions
Square Push Button Switches (SQ3PFS Series)		45	55	Min. A±0.5
Pilot Lights (LQ3RF Series)		37	55	Min. B ±0.5

A-104 Autonics